

KF78 TWIN HEAD COPY ROUTER



FEATURES

- ▶ Two hand operation
- ▶ Ability to route to stops or template
- ▶ Route in 2 planes
- ▶ Easily handles centralized routing needs for long lineals

BENEFITS

- ▶ Increases operator safety
- ▶ Produces precise and accurate routing
- ▶ No need for repositioning or reclamping
- ▶ Excellent for large windows and patio door handles/locks

GIVING YOU GREATER CONTROL THAN EVER BEFORE

KF78 TWIN HEAD COPY ROUTER

Consider GED for all your needs

ADDITIONAL FEATURES

- 1:1 copy routing ratio
- Manual triple stepped copy finger for different cutter diameters
- Pneumatic horizontal and vertical clamping
- (2) Blank Templates

SPECIFICATIONS

Spindle motors (2)	1HP/ 12000RPM/ TEFC
Spindle speeds	12000 RPM
Horizontal routing capacity	11.81" x 3.94" (300 x 100mm) with length stops 10.63" x 2.76" (270 x 70mm) with template
Vertical routing capacity	11.42" x 3.94" (290 x 100mm) with length stops 9.05" x 2.76" (230 x 70mm) with template
Profile clamping capacity	7.09" x 5.91" (180 x 150mm)
Overall dimensions	28" L x 26" W x 50" H
Weight	225 lbs
Electrical requirements	480VAC/ 3Phase / 60Hz / 15FLA
Pneumatic requirements	85PSI / 5CFM

AVAILABLE OPTIONS

- Alternate Voltages Available
- Custom Templates
- Spray Mist Lubrication
- Outboard Support Package
- Self-Centering Mechanism
- Custom Fixturing

Glass Fabrication

IG Spacer Fabrication

Automated Tri-Lite
Assembly System
(ATLAS)

Glass Cutting & Loading

Glass Washing

Muntin Fabrication

Screen Systems

Decorative Glass Solutions

Window Fabrication Cutting

Fabrication

i-3 Smartload Welding
System

ColorTRU Advanced
Profile Coloration
System

Welding

Cleaning

Automated Systems

Custom Engineering

Software Process Solutions

Material Handling Solutions

Training & Support



To learn more, call 330.963.5401, fax 330.963.0584 or visit us at
www.gedusa.com

